

## WAVE POWER LE 5W-40

### Fully Synthetic MID SAPS Passenger Car Motor Oil

**WAVE POWER LE 5W-40** is a high performance fuel saving MID SAPS engine oil based on 100% synthetic technology for use in the latest generation gasoline and diesel engines of passenger car and light vans with or without turbocharger.

**WAVE POWER LE 5W-40** is developed for use in engines which are equipped with or without an exhaust gas after treatment system.

**WAVE POWER LE 5W-40** is based on high performance 100% synthetic base oil in combination with a specially selected additive technology to ensure the following properties:

- Good thermal and oxidation stability.
- MID SAPS technology.
- Good protection against wear, foam and corrosion.
- Low temperature properties, to ensure a smooth cold start.
- Equipped for diesel engines with an exhaust after treatment system.
- Fuel saving properties

**WAVE POWER LE 5W-40** exceeds the following performance criteria:

**Approved** MB-Approval 229.51 VW 502.00/505.00 & 505.01

**Exceeds** API SN/CF ACEA A3/B4, C3 Renault RN 0700/0710  
BMW LL-04

### Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	5W-40
Density @15°C	kg/m <sup>3</sup>	ASTM 4052	854
Kinematic Viscosity @ 40°C	mm <sup>2</sup> /s	ASTM D7042	84.5
Kinematic Viscosity @ 100°C	mm <sup>2</sup> /s	ASTM D7042	14.4
Viscosity Index		ASTM D2270	172
Viscosity CCS @ -30, max	cP	ASTM D5293	6600
Flash Point COC	°C	ASTM D92	>218
Pour Point	°C	ASTM D97	-39
Total Base Number	mgKOH/g	ASTM D2896	7.6
Sulphated Ash	%Wt	ASTM D874	0.8