

WAVE POWER SPECIAL LLV 0W-30

Fully Synthetic MID SAPS Passenger Car Engine oil

WAVE POWER SPECIAL LLV 0W-30 is a high performance fuel saving LOW SAPS long life oil based on 100% synthetic technology for use in gasoline- and diesel engines of passenger cars and light vans where a VAG norm VW 504.00/507.00 has been prescribed.

Remark: not suitable for R5- and V10 TDI engines and engines where VAG norm VW 506.01 is being advised.

WAVE POWER SPECIAL LLV 0W-30 is formulated with high quality synthetic base stocks in combination with an unique additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.
- Extended oil drain interval.
- Also suitable for engines equipped with other catalyst like TWC.

WAVE POWER SPECIAL LLV 0W-30 meets the following performance criteria:

Meets: VW 504 00/507 00 Porsche C30 ACEA C3 BMW LL-04

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	0W-30
Density @15 °C	kg/m ³	ASTM 4052	842
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	60
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	12.2
Viscosity Index		ASTM D2270	203
Viscosity CCS @ -35 °C	cP	ASTM D5293	6030
Flash Point COC	°C	ASTM D92	210
Pour Point	°C	ASTM D7346	-51
Total Base Number	mgKOH/g	ASTM D2896	8.0
Sulphated Ash	%Wt	ASTM D874	0.7
Date Issued: 04-10-2021	Supersedes: -	Revision Nr.: -	

