

WAVE POWER ADVANTAGE 20W-50

Mineral Passenger Car Engine oil

WAVE POWER ADVANTAGE 20W-50 is a high performance mineral engine oil suitable for gasoline-, LPG-, and diesel engines in modern passenger cars and light vans with or without turbochargers.

WAVE POWER ADVANTAGE 20W-50 is based on high performance virgin mineral base oil in combination with a specially selected additive technology to ensure the following properties:

- Good thermal and oxidation stability.
- Stay-in-grade.
- Good protection against wear, foam and corrosion.
- Low temperature properties, to ensure a smooth cold start.

WAVE POWER ADVANTAGE 20W-50 meets the following performance criteria:

API SN ACEA A3/B3 MB 229.1 VW 501.01/505.00

Typical Analysis

| Properties | Unit | Method | Typical Vo | Typical Value | |
|-----------------------------|----------------------------|-----------|------------------|---------------|--|
| | | | | | |
| SAE Grade | | SAE J300 | 20W-50 | 20W-50 | |
| Density @15°C | kg/m³ | ASTM 4052 | 2 866 | | |
| Kinematic Viscosity @ 40°C | mm²/s | ASTM D704 | 142 | 142 | |
| Kinematic Viscosity @ 100°C | mm²/s | ASTM D704 | 17.9 | 17.9 | |
| Viscosity Index | | ASTM D227 | 70 142 | | |
| Viscosity CCS @ -15°C | сР | ASTM D529 | 93 4200 | | |
| Flash Point COC | °C | ASTM D92 | >200 | | |
| Pour Point | °C | ASTM D734 | 46 -33 | | |
| Total Base Number | mgKOH/g | ASTM D289 | 96 9.2 | | |
| Sulphated Ash | %Wt | ASTM D874 | 4 1.1 | | |
| Date Issued: 27-01-2023 | Supersedes: 18-01-2021 Rev | | Revision Nr.: 03 | | |















