

WAVE POWER EXCELLENCE SYNTH LE 5W-30

Fully Synthetic MID SAPS Passenger Car Engine oil

WAVE POWER EXCELLENCE SYNTH LE 5W-30 is a high-performance fuel saving MID SAPS engine oil based on 100% synthetic technology for use in the latest generation gasoline and diesel engines of passenger cars and light vans with or without turbocharger.

WAVE POWER EXCELLENCE SYNTH LE 5W-30 is developed for use in engines which are equipped with or without an exhaust gas after treatment system (DPF, EGR).

WAVE POWER EXCELLENCE SYNTH LE 5W-30 is based on high performance 100% synthetic base oil in combination with a specially selected additive technology to ensure the following properties:

- Good thermal and oxidation stability.
- MID SAPS technology.
- Good protection against wear, foam and corrosion.
- Low temperature properties, to ensure a smooth cold start.
- Equipped for diesel engines with an exhaust after treatment system.
- Fuel saving properties.

WAVE POWER EXCELLENCE SYNTH LE 5W-30 meets the following performance criteria:

Approved: MB-Approval 229.52 MB-Approval 229.51 BMW LL-04

(Pending) (Pending) (Pending)

OV 040 1547 - G30 OV 040 1547 - D30 (Pending) (Pending)

Meets: ACEA C3 API SP RN17

MB 229.3 MB 226.52

Typical Analysis

| Properties | Unit | Method | Typical Value |
|-----------------------------|--------------------|------------------------|---------------|
| | | | |
| SAE Grade | | SAE J300 | 5W-30 |
| Density @15°C | kg/m³ | ASTM 4052 | 851 |
| Kinematic Viscosity @ 40°C | mm ² /s | ASTM D7042 | 66.4 |
| Kinematic Viscosity @ 100°C | mm ² /s | ASTM D7042 | 11.6 |
| Viscosity Index | | ASTM D2270 | 171 |
| Viscosity CCS @ -30°C | сР | ASTM D5293 | 5810 |
| Flash Point COC | °C | ASTM D92 | >201 |
| Pour Point | °C | ASTM D7346 | -39 |
| Total Base Number | mgKOH/g | ASTM D2896 | 9.8 |
| Date Issued: 16-02-2024 | Supersedes: - | des: - Revision Nr.: - | |















