

WAVE POWER ADVANTAGE 15W-50

Semi Synthetic Passenger Car Engine oil

WAVE POWER ADVANTAGE 15W-50 is a high performance semi synthetic engine oil for gasoline- and diesel engines of passenger cars and light vans with or without turbocharger. Not suited for engines equipped with an exhaust gas after treatment system used in modern diesel engines like Diesel Particle Filter (DPF).

WAVE POWER ADVANTAGE 15W-50 formulated with high quality refined mineral and synthetic base stocks in combination with a special additive technology to achieve the following performance:

- Stable Viscosity Index.
- Good protection against rust, corrosion and wear.
- Good dispersancy and detergency properties.
- Good antifoam properties.
- Good thermal- and oxidation stability.

WAVE POWER ADVANTAGE 15W-50 meets the following performance criteria:

API SN

ACEA A3/B3

MB 229.1

VW 501.01/505.00

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	15W-50
Density @15 °C	kg/m ³	ASTM 4052	858
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	118
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	17.4
Viscosity Index		ASTM D2270	162
Viscosity CCS @ -20 °C	cP	ASTM D5293	3500
Flash Point COC	°C	ASTM D92	>200
Pour Point	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	9.6
Sulphated Ash	%Wt	ASTM D874	1.1
Date Issued: 27-01-2023	Supersedes: 19-01-2021	Revision Nr.: 02	

