

WAVE POWER EXCELLENCE 15W-40

Mineral Passenger Car Engine oil

WAVE POWER EXCELLENCE 15W-40 is a high quality mineral engine oil suitable for gasoline-, LPG-, and diesel engines in modern passenger cars and light vans with or without turbochargers. This product is unsuitable for diesel engines equipped with a Diesel Particulate Filter (DPF).

WAVE POWER EXCELLENCE 15W-40 is based on high performance mineral base oil in combination with a specially selected additive technology to ensure the following properties:

- Good thermal and oxidation stability.
- Stay-in-grade.
- Good protection against wear, foam and corrosion.
- Low temperature properties, to ensure a smooth cold start.

WAVE POWER EXCELLENCE 15W-40 meets the following performance criteria:

API SN/CF ACEA A3/B4 MB 229.1 VW 501.01/505.00 PSA B71 2295

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	15W-40
Density @15 °C	kg/m ³	ASTM 4052	859
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	93.55
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	14.0
Viscosity Index		ASTM D2270	154
Viscosity CCS @ -20 °C	cP	ASTM D5293	3590
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-33
Total Base Number	mgKOH/g	ASTM D2896	10.1
Sulphated Ash	%Wt	ASTM D874	0.96
Date Issued: 24-6-2021	Supersedes: 22-03-2019	Revision Nr.: 02	

