

## **WAVE POWER EXCELLENCE 5W-40**

Fully Synthetic Passenger Car Engine oil

**WAVE POWER EXCELLENCE 5W-40** is a modern 100% synthetic engine oil for use in high output, turbocharged, supercharged multi valve fuel injected engines in passenger cars, SUVs and light vans.

**WAVE POWER EXCELLENCE 5W-40** is formulated with high quality synthetic base stocks in combination with an unique additive technology to achieve the following performance:

- Long drain intervals
- High protection against deposits and "sludge" formation
- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High Viscosity Index

**WAVE POWER EXCELLENCE 5W-40** meets the following performance criteria:

Approved	MB-Approval 229.5	VW 502.00/505.00	
Meets	API SP	ACEA A3/B4	MB 226.5
	MB 229.3	GM-LL-025-A	GM-LL-025-B
	Renault RN 0700/0710	PSA B71 2296	BMW LL-01 (<-2019)

## **Typical Analysis**

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	5W-40
Density @15°C	kg/m³	ASTM 4052	850
Kinematic Viscosity @ 40°C	mm²/s	ASTM D7042	2 85
Kinematic Viscosity @ 100°C	mm²/s	ASTM D7042	2 14.3
Viscosity Index		ASTM D2270	) 175
Viscosity CCS @ -30°C	сР	ASTM D5293	3 5820
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7340	5 -36
Total Base Number	mgKOH/g	ASTM D2890	5 11.4
Sulphated Ash	%Wt	ASTM D874	1.25
Date Issued: 15-08-2022	Supersedes: 9-12-2021		Revision Nr.: 04