

TIDAL POWER HD 15W-40

Mineral Heavy Duty Diesel Engine oil

TIDAL POWER HD 15W-40 is a high performance universal mineral oil designed for high loaded diesel engines in light- and heavy commercial vehicles working under severe operating conditions through the whole year and is formulated for use in Euro-1, Euro-2 and Euro-3 engines equipped with EGR and/or SCR. This product is not suitable for vehicles equipped with a Diesel Particulate Filter (DPF).

TIDAL POWER HD 15W-40 is formulated with high refined solvent base stocks in combination with a special additive package to reach the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- High anti-foam, anti-wear and anti-corrosion properties.
- Excellent protection against Bore Polishing.
- Not suitable for engine equipped with a Diesel Particulate Filter (DPF).

TIDAL POWER HD 15W-40 meets the following performance criteria:

API CG-4
Volvo VDS

ACEA E2
Renault RD

MB 228.1
MTU Type 1

MAN M271

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	15W-40
Density @15°C	kg/m ³	ASTM 4052	873
Kinematic Viscosity @ 40°C	mm ² /s	ASTM D7042	103.9
Kinematic Viscosity @ 100°C	mm ² /s	ASTM D7042	14.1
Viscosity Index		ASTM D2270	139
Viscosity CCS @ -20°C, max	cP	ASTM D5293	7000
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	8.6
Sulphated Ash	%Wt	ASTM D874	1.26
Date Issued: 30-08-2018	Supersedes: 08-03-2018	Revision Nr.: 02	

