

TIDAL POWER HD 20W-50

Mineral Heavy Duty Diesel Engine oil

TIDAL POWER HD 20W-50 is a high performance universal engine oil designed for high loaded diesel engines in light- and heavy commercial vehicles working under severe operating conditions through the whole year for use in Euro-1, Euro-2 and Euro-3 engines equipped with EGR and/or SCR. This product is not suitable for vehicles equipped with a Diesel Particulate Filter (DPF).

TIDAL POWER HD 20W-50 is formulated with high refined solvent mineral base stock in combination with a special additive package to reach the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- High anti-foam, anti-wear and anti-corrosion properties.
- Excellent protection against Bore Polishing.

TIDAL POWER HD 20W-50 meets the following performance criteria:

API CG-4	ACEA E2	MB 228.1	MAN M 271
Volvo VDS	MTU Type 1	Renault RD	

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	20W-50
Density @15°C	kg/m³	ASTM 4052	879
Kinematic Viscosity @ 40°C	mm²/s	ASTM D704	2 146
Kinematic Viscosity @ 100°C	mm²/s	ASTM D704	2 18.2
Viscosity Index		ASTM D227	0 139
Viscosity CCS @ -15°C, max.	сР	ASTM D529	3 9500
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D734	6 -31
Total Base Number	mgKOH/g	ASTM D289	6 8.6
Sulphated Ash	%Wt	ASTM D874	1.26
Date Issued: 17-6-2021	Supersedes: 09-05-2018		Revision Nr.: 02