

AUTOGEAR POWER MP 75W-90

Automotive Multi Purpose Gear Oil

AUTOGEAR POWER MP 75W-90 is a high performance multi purpose gear lubricant designed to provide excellent lubrication in a wide range of automotive transmissions, axles and final drives.

AUTOGEAR POWER MP 75W-90 is based on a high quality refined virgin base oil in combination with a special additive package to ensure the following properties:

- Good extreme pressure and anti-wear properties.
- High thermal- and oxidation stability.
- Effective rust, wear and corrosion protection.
- Better low temperature provides easy start-up at low ambient temperatures.
- Good anti-foam properties ensure film strength for effective lubrication.
- Excellent seal compatibility.

AUTOGEAR POWER MP 75W-90 meets the following performance criteria:

API GL-5	MIL-L-2105D	MAN 342 M1	MB 235.0
Volvo 97310	ZF TE-ML 07A, 16B, 17	7B, 21A	

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J306	75W-90
Density @15°C	kg/m³	ASTM 4052	865
Kinematic Viscosity @ 40°C	mm²/s	ASTM D7042	103.4
Kinematic Viscosity @ 100°C	mm²/s	ASTM D7042	15.7
Viscosity Index		ASTM D2270	162
Viscosity Brookfield @-55°C	сР	ASTM D5293	<150000
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-52
Date Issued: 27-08-2020	Supersedes: -	R	evision Nr.: -