

AUTOGEAR POWER LS 80W-90

“Limited Slip” Automotive Gear Oil

AUTOGEAR POWER LS 80W-90 is an extra high performance extreme pressure type automotive gear lubricant specially developed for use in modern high performance passenger cars, sports utility vehicles, vans and light duty trucks with limited slip differentials.

AUTOGEAR POWER LS 80W-90 is based on a high quality mineral virgin base oil in combination with a special additive package to ensure the following properties:

- Exceptional thermo-oxidative stability.
- Exceptional load bearing characteristics.
- Effective rust and corrosion protection.
- Excellent limited slip performance to reduce chatter and improves traction.
- Outstanding low temperature fluidity provides smoother shifting at low ambient temperatures.
- Exceptional shear stable.
- Good frictional properties provide improved fuel economy and smoother shift ability

AUTOGEAR POWER LS 80W-90 meets the following performance criteria:

API GL-5 MAN 342 M1/M2 Volvo 1273.10 MIL-L-2105D
Arvin Meritor ZF TE-ML 05C, 07A, 08, 12E, 16E, 17B, 19B, 21C

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J306	80W-90
Density @15°C	kg/m ³	ASTM 4052	887
Kinematic Viscosity @ 40°C	mm ² /s	ASTM D7042	131
Kinematic Viscosity @ 100°C	mm ² /s	ASTM D7042	14.4
Viscosity Index		ASTM D2270	109
Flash Point COC	°C	ASTM D92	>200
Pour Point	°C	ASTM D7346	-33
Date Issued: 26-1-2021	Supersedes: 25-01-2018	Revision Nr.: 02	

