

## **GEAR POWER TO-4 10W**

## **Heavy Duty Powershift Transmission Fluid**

**GEAR POWER TO-4 10W** is specifically designed for powershift transmissions, final drives and wet brakes on heavy duty off-highway equipment used in earthmoving, mining logging, road transport and agricultural applications.

**GEAR POWER TO-4 10W** is formulated with a high refined solvent mineral base stock in combination with a special additive package to reach the following properties.

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- High anti-foam, anti-wear and anti-corrosion properties.
- Excellent protection against Bore Polishing.
- Extended drain intervals possible.

## **GEAR POWER TO-4 10W** meets the following performance criteria:

Caterpillar TO-4 Komatsu KES 07.868.1 Allison C-4 API CF-2/CF ZF TE-ML 03C Komatsu Dresser DANA Powershift transmissions Vickers 35VQ25

**Typical Analysis** 

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	10W
Density @15°C	kg/m3	ASTM D4052	862
Kin. Viscosity @40°C	mm2/s	ASTM D7042	41.5
Kin. Viscosity @100°C	mm2/s	ASTM D7042	6.8
Viscosity Index		ASTM D2270	121
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	5.5
Date Issued: 16-6-2021	Supersedes: 04-08-2016 Revisi		sion Nr.: 02















