

## ATF POWER DX III

### Automatic transmission fluid

**ATF POWER DX III** is a high quality universal fluid to be used in automatic transmission, torque convertors and power steering of passenger cars, light vans and commercial vehicles.

**ATF POWER DX III** is formulated on high refined solvent mineral and synthetic base stock in combination with an unique additive package to reach the following properties.

- Excellent thermal- and oxidation stability.
- Special friction modifiers.
- Very High Viscosity Index.
- Low pour point.
- Excellent shifting at very low and high temperatures.
- Excellent protection against the forming corrosion, foam and wear.

**ATF POWER DX III** meets the following performance criteria:

DEXRON III F/G/H	Allison C4	CAT TO-2	MAN 339 Z1/Z2
MAN 339 V1/V2	MB 236.10/236.9/236.7/236.5/236.1		Voith 55.6335
Volvo 97341	Mercon	ZF 02F/03D/04D	ZF 11A/11B/14B/16L

### Typical Analysis

Properties	Unit	Method	Typical Value
Color		visual	Red
Density @15 °C	kg/m <sup>3</sup>	ASTM 4052	845
Kinematic Viscosity @ 40 °C	mm <sup>2</sup> /s	ASTM D7042	35
Kinematic Viscosity @ 100 °C	mm <sup>2</sup> /s	ASTM D7042	7.5
Viscosity Index		ASTM D2270	189
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-51
Date Issued: 26-1-2021	Supersedes: 01-11-2016	Revision Nr.: 02	

