

## ATF POWER DX VI

### Automatic transmission fluid

**ATF POWER DX VI** is a high quality universal fluid based on 100% synthetic base stocks to be used in automatic transmission, torque converters and power-steering of passenger cars, light vans and commercial vehicles where a GM Dexron VI specification is required. **ATF POWER DX VI** is backwards compatible where Dexron II and Dexron III are required.

**ATF POWER DX VI** is formulated on high refined synthetic base stock in combination with an unique additive package to reach the following properties.

- Excellent thermal- and oxidation stability.
- Special friction modifiers.
- Very High Viscosity Index.
- Low pour point.
- Excellent shifting at very low and high temperatures.
- Excellent protection against the forming corrosion, foam and wear.

**ATF POWER DX VI** meets the following performance criteria:

GM Dexron VI

Voith 55.6335.3X (G607)

### Typical Analysis

Properties	Unit	Method	Typical Value
Color		visual	Red
Density @15 °C	kg/m <sup>3</sup>	ASTM 4052	842
Kinematic Viscosity @ 40 °C	mm <sup>2</sup> /s	ASTM D7042	28.1
Kinematic Viscosity @ 100 °C	mm <sup>2</sup> /s	ASTM D7042	5.9
Viscosity Index		ASTM D2270	154
Flash Point COC	°C	ASTM D92	180
Pour Point	°C	ASTM D7346	-46
Date Issued: 17-6-2021		Supersedes: 05-08-2016	Revision Nr.: 01

