

## **AUTOGEAR POWER TX 75W-90**

## **Fully Synthetic Universal Transmission Oil**

**AUTOGEAR POWER TX 75W-90** is a high quality fully synthetic transmission oil designed to meet the demanding requirements of heavy duty commercial vehicles and off-highway equipment operating in most severe operating conditions. Suitable for both manual transmissions and automated transmission (like for example Volvo I-shift)

**AUTOGEAR POWER TX 75W-90** is based on high quality 100% synthetic Poly Alpha Olefin (PAO) base oils in combination with a special additive package to ensure the following properties:

- Exceptional thermo-oxidative stability.
- Exceptional load bearing characteristics.
- Exceptional shear stability
- Effective rust and corrosion protection.
- Outstanding low temperature fluidity provides smoother shifting at low ambient temperatures.
- Superior frictional properties provide improved fuel economy and smoother shiftability

## **AUTOGEAR POWER TX 75W-90** meets the following performance criteria:

API GL-4 Merito O81 MB 235.11 Volvo 97305 Volvo 97307 Volvo 97319 Eaton Synthetic (500.000km/3 years)

## **Typical Analysis**

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	75W-90
Density @15°C	kg/m³	ASTM 4052	852
Kinematic Viscosity @ 40°C	mm <sup>2</sup> /s	ASTM D7042	96
Kinematic Viscosity @ 100°C	mm <sup>2</sup> /s	ASTM D7042	15.8
Viscosity Index		ASTM D2270	176
Brookfield Viscosity @-40°C	сР	ASTM D2983	350000
Flash Point COC	°C	ASTM D92	>200
Pour Point	°C	ASTM D7346	-63
Date Issued: 12-01-2024	Supersedes: -	·	Revision Nr.: -















