

HYDRA POWER PLUS 100

Hydraulic Oil

HYDRA POWER PLUS 100 is a premium quality anti-wear hydraulic oil specially developed for applications like hydraulic and power transmission subjected to wide range of temperature or where small viscosity change with fluctuating temperature is required.

HYDRA POWER PLUS 100 is formulated with high quality virgin mineral base stocks in combination with a special additive technology to achieve the following performance:

- Exceptional anti-wear property results in longer component life reducing costs.
- Extremely High Viscosity Index assures equipment protection at cold start-up temperatures and at high operating temperatures.
- Excellent shear stability minimizes viscosity loss over time and exhibits "stay-in-grade" performance under high shear conditions.
- Excellent thermo-oxidative.
- Superior demulsibility helps in faster separation of water from oil and resists formation of emulsions.
- Special rust & corrosion inhibitors protect multi-metallurgy components even in presence of moisture.
- Rapid air release property due to non-silicone anti-foam technology to minimizes chances of pump cavitations leading to trouble free operations.
- Compatible with multi-metals & most sealing materials commonly used in hydraulic systems.

HYDRA POWER PLUS 100 meets the following performance criteria:

DIN 51524/3 HVLP AFNOR NFE 48-603 ISO 11158 HV Vickers M-2950
I-286-S US Steel 127, 136

Typical Analysis

Properties	Unit	Method	Typical Value
ISO VG Grade		ISO 3448	100
Density @15 °C	kg/m ³	ASTM D4052	880
Kin. Viscosity @40 °C	mm ² /s	ASTM D7042	101
Kin. Viscosity @100 °C	mm ² /s	ASTM D7042	15.3
Viscosity Index		ASTM D2270	161
Flash Point COC, min	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-42
FZG Fail Load Stage, min		DIN 51354-2	11
Demulsibility @82 °C	Minutes	DIN 51599	Pass
Date Issued: 10-6-2021		Supersedes: 17-10-2016	Revision Nr.: 01

