

HYDRA POWER 68

Hydraulic Oil

HYDRA POWER 68 is a high performance anti-wear hydraulic oil developed for high pressure hydraulic systems operating under moderate to severe conditions in mobile and industrial service.

HYDRA POWER 68 is formulated with high quality virgin mineral base stocks in combination with a special additive technology to achieve the following performance:

- Exceptional anti-wear property results in longer component life reducing costs.
- Excellent shear stability minimizes viscosity loss over time and exhibits "stay-in-grade" performance under high shear conditions.
- Excellent thermo-oxidative.
- Superior demulsibility helps in faster separation of water from oil and resists formation of emulsions.
- Special rust & corrosion inhibitors protect multi-metallurgy components even in presence of moisture.
- Rapid air release property due to non-silicone anti-foam technology to minimizes chances of pump cavitations leading to trouble free operations.
- Compatible with multi-metals & most sealing materials commonly used in hydraulic systems.

HYDRA POWER 68 meets the following performance criteria:

DIN 51524/2 HLP AFNOR NFE 48-603 ISO 11158 HMVickers M-2950
I-286-S US Steel 127, 136 Denison HF-2 Cincinnati P-69

Typical Analysis

Properties	Unit	Method	Typical Value
ISO VG Grade		ISO 3448	68
Density @15°C	kg/m ³	ASTM D4052	878
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	69
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	9
Viscosity Index		ASTM D2270	104
Flash Point COC, min	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-35
FZG Fail Load Stage, min		DIN 51354-2	11
Demulsibility @54°C	Minutes	DIN 51599	Pass
Date Issued: 10-6-2021		Supersedes: 11-10-2016	Revision Nr.: 01

