

## **INDUSTRIAL GEAR POWER 320**

**Industrial Gear Oil** 

**INDUSTRIAL GEAR POWER 320** is a high performance extreme pressure gear oil which is developed for lubrication of heavy duty industrial gears working under severe operating conditions.

**INDUSTRIAL GEAR POWER 320** is based on high quality virgin mineral base oil in combination with an unique additive package to ensure the following properties:

- Excellent load carrying capability protects gears against scuffing and wear and offers long equipment life and reduced maintenance costs.
- High thermo-oxidative stability helps resist deposit formation, provides enhanced system cleanliness and enables longer service intervals.
- Provides effective rust and corrosion protection to all gearbox components.
- Excellent demulsibility property enables trouble-free operation in conditions encountering water/ moisture.

**INDUSTRIAL GEAR POWER 320** meets the following performance criteria:

DIN 51517-3 CLP ISO 1292501 CKC AGMA 9005 E-02 US Steel 224 David Brown \$1.53.101

Properties	Unit	Method	1	Typical Value	
Density @15°C	kg/m3	ASTM D4052		898	
Kin. Viscosity @40°C	mm2/s	ASTM D7042		320	
Kin. Viscosity @100°C	mm2/s	ASTM D7042		23.8	
Viscosity Index		ASTM D2270		94	
Flash Point COC, min	°C	ASTM D92		>201	
Pour Point	°C	ASTM D7346		-12	
FZG Fail Load Stage, min		DIN 51354-2		12	
Demulsibility @82°C		DIN 51599		15	
Date Issued: 10-6-2021	Supersedes: 17	Supersedes: 17-10-2016		Revision Nr.: 01	

## **Typical Analysis**