

INDUSTRIAL GEAR POWER 460

Industrial Gear Oil

INDUSTRIAL GEAR POWER 460 is a high performance extreme pressure gear oil which is developed for lubrication of heavy duty industrial gears working under severe operating conditions.

INDUSTRIAL GEAR POWER 460 is based on high quality virgin mineral base oil in combination with an unique additive package to ensure the following properties:

- Excellent load carrying capability protects gears against scuffing and wear and offers long equipment life and reduced maintenance costs.
- High thermo-oxidative stability helps resist deposit formation, provides enhanced system cleanliness and enables longer service intervals.
- Provides effective rust and corrosion protection to all gearbox components.
- Excellent demulsibility property enables trouble-free operation in conditions encountering water/ moisture.

INDUSTRIAL GEAR POWER 460 meets the following performance criteria:

DIN 51517-3 CLP ISO 1292501 CKC AGMA 9005 E-02 US Steel 224 David Brown \$1.53.101

Typical Analysis

Properties	Unit	Method	Тур	ical Value
Density @15°C	kg/m3	ASTM D4052		903
Kin. Viscosity @40°C	mm2/s	ASTM D7042		474
Kin. Viscosity @100°C	mm2/s	ASTM D7042		30.9
Viscosity Index		ASTM D2270		96
Flash Point COC, min	°C	ASTM D92		>201
Pour Point	°C	ASTM D7346		-15
FZG Fail Load Stage, min		DIN 51354-2		12
Demulsibility @82°C	max	DIN 51599		15
Date Issued: 10-6-2021	Supersedes: 17	7-10-2016	Revision Nr.: 01	















