

LHM FLUID

Special LHM Fluid

LHM FLUID is a hydraulic oil which has been especially developed for application in brake systems, levelling and hydraulic controlled clutches in a number of Citroën, Bentley and Rolls-Royce cars. Also, suitable for certain industrial hydraulic systems, where anti-wear properties are required.

LHM FLUID should never be used in braking systems other than those prescribed above.

LHM FLUID is based on high quality virgin mineral base oil in combination with an unique additive package to ensure the following properties:

- Excellent thermo- and oxidation stability.
- High resistance against rust and corrosion.
- Extreme fluidity at low temperature.
- Exceptional high and stable Viscosity Index.
- Very low pour point.
- Not hygroscopic.

LHM FLUID meets the following performance criteria:

PSA B71 2710

ISO 7308

LHM

LHM+

Typical Analysis

Properties	Unit	Method	Typical Value
Colour		Visual	Green
Density @15 °C	kg/m ³	ASTM D4052	840
Kin. Viscosity @40 °C	mm ² /s	ASTM D7042	18
Kin. Viscosity @100 °C	mm ² /s	ASTM D7042	6.3
Viscosity Index		ASTM D2270	353
Flash Point COC, min	°C	ASTM D92	110
Pour Point	°C	ASTM D7346	-60
Date Issued: 10-6-2021	Supersedes: 17-10-2016	Revision Nr.: 01	

