

HANSA POWER MGX 15W-40

Marine 4-Stroke High Speed Diesel Engine oil

HANSA POWER MGX 15W-40 is a premium quality marine engine oil developed to meet the performance requirements of modern turbocharged and naturally aspirated marine diesel engines operating on distillate diesel fuel.

HANSA POWER MGX 15W-40 is formulated with high refined solvent base stocks in combination with a special additive package to reach the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- High anti-foam, anti-wear and anti-corrosion properties.
- Excellent protection against Bore Polishing.
- Not suitable for engine equipped with a Diesel Particulate Filter (DPF).

HANSA POWER MGX 15W-40 meets the following performance criteria:

API CH-4

ACEA E2 (level)

MB 228.3

MAN M 3275

Volvo VDS

MTU Type 2

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	15W-40
Density @15°C	kg/m ³	ASTM 4052	875
Kinematic Viscosity @ 40°C	mm ² /s	ASTM D7042	99
Kinematic Viscosity @ 100°C	mm ² /s	ASTM D7042	13.9
Viscosity Index		ASTM D2270	142
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-34
Total Base Number	mgKOH/g	ASTM D2896	8.7
Sulphated Ash	%Wt	ASTM D874	1.26
Date Issued: 15-6-2021	Supersedes: 24-10-2016	Revision Nr.: 01	

