

WAVE POWER PERFORMANCE 5W-20

Semi-Synthetic Passenger Car Motor Oil

WAVE POWER PERFORMANCE 5W-20 is an universal high performance fuel saving oil based on semi-synthetic technology for use in gasoline engines of passenger car and light vans with or without turbocharger.

WAVE POWER PERFORMANCE 5W-20 is formulated with high quality hydro-treated mineral and synthetic base stocks in combination with an unique additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.

WAVE POWER PERFORMANCE 5W-20 is suitable for use where the following specifications are required:

API SN/CF

Typical Analysis

| Properties | Unit | Method | Typical Value |
|------------------------------|--------------------|---------------|---------------|
| SAE Grade | | SAE J300 | 5W-20 |
| Density @15 °C | kg/m ³ | ASTM 4052 | 847 |
| Kinematic Viscosity @ 40 °C | mm ² /s | ASTM D7042 | 44.7 |
| Kinematic Viscosity @ 100 °C | mm ² /s | ASTM D7042 | 8.3 |
| Viscosity Index | | ASTM D2270 | 168 |
| Viscosity CCS @ -30 °C | cP | ASTM D5293 | 3120 |
| Flash Point COC | °C | ASTM D92 | >201 |
| Pour Point | °C | ASTM D7346 | -42 |
| Total Base Number | mgKOH/g | ASTM D2896 | 8.5 |
| HTHS 150 °C | mPa.s | ASTM D4683 | 2.7 |
| Date Issued: 2-3-2022 | Supersedes: | Revision Nr.: | |

