

SPORT POWER 4T 5W-40

Fully Synthetic 4-Stroke Motorcycle Oil

SPORT POWER 4T 5W-40 is a premium 4-stroke gasoline engine oil developed specifically to meet the special requirements of latest high performance liquid and air cooled 4-stroke motorcycles. It provides excellent protection to engine, gearbox and wet clutch used in 4-stroke motorcycles and ensures highest degree of reliability even under severe operating conditions and temperatures.

SPORT POWER 4T 5W-40 is based on top quality synthetic PAO/Ester base oils in combination with a special selected additive package to obtain the following properties:

- Outstanding thermo-oxidative stability.
- Exceptional anti-wear, anti-rust and anti-corrosion properties.
- Controlled frictional properties eliminate clutch slippage.
- Increased power/ fuel economy and improves drivability.
- Excellent dispersancy and detergency properties.
- Excellent shear stability maintains viscosity under high temperature high shear environment and provides improved wear protection.
- Outstanding low temperature properties enable easy starting at low ambient temperatures and ensure effective lubrication and wear protection at start up.
- Low volatility characteristics reduce oil consumption and hydrocarbon pollution.

SPORT POWER 4T 5W-40 meets the following performance criteria:

API SN JASO MA2

Typical Analysis

| Properties | Unit | Method | Typical Value |
|-----------------------------|---------------|-------------------------------|---------------|
| | | | |
| SAE Grade | | SAE J300 | 5W-40 |
| Density @15°C | kg/m³ | ASTM 4052 | 849 |
| Kinematic Viscosity @ 40°C | mm²/s | ASTM D7042 | 86.5 |
| Kinematic Viscosity @ 100°C | mm²/s | ASTM D7042 | 13.5 |
| Viscosity Index | | ASTM D2270 | 158 |
| Flash Point COC | °C | ASTM D92 | 201 |
| Pour Point | °C | ASTM D7346 | -48 |
| Total Base Number | mgKOH/g | ASTM D2896 | 8.6 |
| Date Issued: 02-12-2022 | Supersedes: - | Supersedes: - Revision Nr.: - | |