

PERFORMANCE POWER 4T 15W-40

Semi Synthetic 4-Stroke Motorcycle Oil

PERFORMANCE POWER 4T 15W-40 is a 4-stroke gasoline engine oil developed specifically to meet the special requirements of latest high performance liquid and air cooled 4-stroke motorcycles. It provides excellent protection to engine, gearbox and wet clutch used in 4-stroke motorcycles and ensures highest degree of reliability even under severe operating conditions and temperatures.

PERFORMANCE POWER 4T 15W-40 is based on excellent quality hydrotreated mineral and synthetic base oils in combination with a special selected additive package to obtain the following properties:

- Excellent thermo-oxidative stability.
- Very good anti-wear, anti-rust and anti-corrosion properties.
- Controlled frictional properties eliminate clutch slippage.
- Excellent dispersancy and detergency properties.
- Very good shear stability maintains viscosity under high temperature high shear environment and provides improved wear protection.
- Outstanding low temperature properties enable easy starting at low ambient temperatures and ensure effective lubrication and wear protection at start up.
- Low volatility characteristics reduce oil consumption and hydrocarbon pollution.

PERFORMANCE POWER 4T 15W-40 meets the following performance criteria:

API SN JASO MA2

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	15W-40
Density @15°C	kg/m ³	ASTM 4052	860
Kinematic Viscosity @ 40°C	mm ² /s	ASTM D7042	91.3
Kinematic Viscosity @ 100°C	mm ² /s	ASTM D7042	13.6
Viscosity Index		ASTM D2270	151
Flash Point COC	°C	ASTM D92	201
Pour Point	°C	ASTM D7346	-33
Total Base Number	mgKOH/g	ASTM D2896	9.4
Date Issued: 02-12-2022	Supersedes: -	Revision Nr.: -	

