7306 - AUTOGEAR POWER MP 80W-90

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Issue date: 13-1-2012 Revision date: 15-8-2019 Supersedes: 28-2-2019 Version: 1.5

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	:	Mixture
Product name	:	7306 - AUTOGEAR POWER MP 80W-90
Product code	:	73060
Type of product	:	Lubricant
Product group	:	Industrial

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Function or use category : Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

North Sea Lubricants B.V.
Ampèrestraat 5
3846AN Harderwijk - The Netherlands
T +31 651345369
support@northsealubricants.com - www.northsealubricants.com

1.4. Emergency telephone number

Emergency number : +31 (0)786527652
Monday to Friday: 09:00 - 16:00 (CET)

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals-24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	+44 20 7188 7188	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin sensitisation, Category 1	H317
Hazardous to the aquatic environment — Chronic Hazard, Category 3	H412

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :

GHS07

Signal word (CLP) : Warning

Hazardous ingredients : Amines, C12-14-tert-alkyl

Hazard statements (CLP) : H317 - May cause an allergic skin reaction.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) : P261 - Avoid breathing dust, fume, gas, mist, spray, vapours.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, eye protection, face protection.
P302+P352 - IF ON SKIN: Wash with plenty of water.
P321 - Specific treatment (see supplemental first aid instruction on this label).

2.3. Other hazards

Other hazards not contributing to the classification : Flammable liquids. Prolonged or repeated skin contact with the material will remove natural oils which leads to a dermatitis. Spills of this product present a serious slipping hazard.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] substance with a Community workplace exposure limit (Note L)	(CAS-No.) 64742-65-0 (EC-No.) 265-169-7 (EC Index-No.) 649-474-00-6 (REACH-no) 01-2119471299-27	50 – 75	Not classified
Amines, C12-14-tert-alkyl	(CAS-No.) 68955-53-3 (EC-No.) 273-279-1 (REACH-no) 01-2119456798-18	0,1 – 0,5	Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 2 (Inhalation), H330 Skin Corr. 1B, H314 Skin Sens. 1A, H317 STOT SE 3, H335 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Mineral oil substance with a Community workplace exposure limit		0,1 – 0,5	Not classified

(Z)-octadec-9-enylamine	(CAS-No.) 112-90-3 (EC-No.) 204-015-5 (EC Index-No.) 612-283-00-3	0,01 – 0,5	Acute Tox. 4 (Oral), H302 Asp. Tox. 1, H304 STOT SE 3, H335 STOT RE 2, H373 Skin Corr. 1B, H314 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)

Note L : The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 'Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method', Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.
Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with plenty of water.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : After adequate first aid, no further treatment is required unless symptoms reappear.
Symptoms/effects after skin contact : After adequate first aid, no further treatment is required unless symptoms reappear.
Symptoms/effects after eye contact : After adequate first aid, no further treatment is required unless symptoms reappear.
Symptoms/effects after ingestion : After adequate first aid, no further treatment is required unless symptoms reappear.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Eliminate all ignition sources if safe to do so.
Emergency procedures : Ventilate spillage area.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Wear suitable protective clothing, gloves and eye/face protection. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.
Storage temperature : 50 °C
Storage area : Store away from heat. Store in a well-ventilated place.
Special rules on packaging : Store in a closed container. Keep only in original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Amines, C12-14-tert-alkyl (68955-53-3)	
EU - Occupational Exposure Limits	
IOELV TWA (ppm)	1 ppm
IOELV STEL (ppm)	2,5 ppm

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)	
EU - Occupational Exposure Limits	
IOELV TWA (mg/m³)	5 mg/m³
IOELV STEL (mg/m³)	10 mg/m³
Bulgaria - Occupational Exposure Limits	
OEL TWA (mg/m³)	5 mg/m³
OEL STEL (mg/m³)	10 mg/m³
Croatia - Occupational Exposure Limits	
GVI (granična vrijednost izloženosti) (mg/m³)	5 mg/m³
KGVI (kratkotrajna granična vrijednost izloženosti) (mg/m³)	10 mg/m³
Czech Republic - Occupational Exposure Limits	
Expoziční limity (PEL) (mg/m³)	5 mg/m³
Expoziční limity (NPK-P) (mg/m³)	10 mg/m³

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)	
Denmark - Occupational Exposure Limits	
Grænseværdie (langvarig) (mg/m³)	1 mg/m³
Netherlands - Occupational Exposure Limits	
Grenswaarde TGG 8H (mg/m³)	5 mg/m³

Mineral oil	
EU - Occupational Exposure Limits	
IOELV TWA (mg/m³)	5 mg/m³
Belgium - Occupational Exposure Limits	
Limit value (mg/m³)	5 mg/m³
Short time value (mg/m³)	10 mg/m³
Bulgaria - Occupational Exposure Limits	
OEL TWA (mg/m³)	5 mg/m³
Czech Republic - Occupational Exposure Limits	
Expoziční limity (PEL) (mg/m³)	5 mg/m³
Expoziční limity (NPK-P) (mg/m³)	10 mg/m³
Finland - Occupational Exposure Limits	
HTP-arvo (8h) (mg/m³)	5 mg/m³
Greece - Occupational Exposure Limits	
OEL TWA (mg/m³)	5 mg/m³
Latvia - Occupational Exposure Limits	
OEL TWA (mg/m³)	5 mg/m³
Lithuania - Occupational Exposure Limits	
IPRV (mg/m³)	1 mg/m³
TPRV (mg/m³)	3 mg/m³
Netherlands - Occupational Exposure Limits	
Grenswaarde TGG 8H (mg/m³)	5 mg/m³
Poland - Occupational Exposure Limits	
NDS (mg/m³)	5 mg/m³
NDSCh (mg/m³)	10 mg/m³
Spain - Occupational Exposure Limits	
VLA-ED (mg/m³)	5 mg/m³
VLA-EC (mg/m³)	10 mg/m³
Sweden - Occupational Exposure Limits	
nivågränsvärde (NVG) (mg/m³)	1 mg/m³
kortidsvärde (KTV) (mg/m³)	3 mg/m³
USA - ACGIH - Occupational Exposure Limits	
ACGIH TWA (mg/m³)	5 mg/m³
ACGIH STEL (mg/m³)	10 mg/m³

8.2. Exposure controls

Appropriate engineering controls:

Use adequate ventilation to keep oil mist below applicable standard. Use splash goggles when eye contact due to splashing is possible. Ocular shower with suitable liquid.

Personal protective equipment:

Gloves. Safety glasses. Protective clothing. Avoid all unnecessary exposure.

Materials for protective clothing:
Wear suitable protective clothing

Hand protection:
Breakthrough time : refer to the recommendations of the supplier

Eye protection:
Chemical goggles or safety glasses. Use splash goggles when eye contact due to splashing is possible. EN 166

Skin and body protection:
Avoid prolonged and repeated contact with skin. If repeated skin contact or contamination of clothing is likely, protective clothing should be worn

Respiratory protection:
Where excessive vapour, mist, or dust may result, use approved respiratory protection equipment. Particle filter. EN 143

Personal protective equipment symbol(s):

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Liquid
Colour	:	light brown.
Odour	:	No data available
Odour threshold	:	No data available
pH	:	No data available
Relative evaporation rate (butylacetate=1)	:	No data available
Melting point	:	Not applicable
Freezing point	:	-27 °C
Boiling point	:	No data available
Flash point	:	> 200 °C
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Flammability (solid, gas)	:	Not applicable
Vapour pressure	:	No data available
Relative vapour density at 20 °C	:	No data available
Relative density	:	No data available
Density	:	902 kg/m³ @15°C
Solubility	:	insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	:	No data available
Viscosity, kinematic	:	162 mm²/s @40°C

Viscosity, dynamic	:	No data available
Explosive properties	:	No data available
Oxidising properties	:	No data available
Explosive limits	:	No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	:	Not classified
Acute toxicity (dermal)	:	Not classified
Acute toxicity (inhalation)	:	Not classified

(Z)-octadec-9-enylamine (112-90-3)	
LD50 oral (rat)	1689 mg/kg bodyweight

Amines, C12-14-tert-alkyl (68955-53-3)	
LD50 oral (rat)	612 mg/kg
LD50 dermal (rat)	251 mg/kg bodyweight
LC50 inhalation (rat) (mg/l)	1,19 mg/l/4h

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)	
LD50 oral (rat)	> 5000 mg/kg bodyweight
LD50 dermal (rabbit)	> 5000 mg/kg
LC50 inhalation (rat) (Vapours - mg/l/4h)	> 5,53 mg/l/4h

Mineral oil	
LD50 oral (rat)	> 5000 mg/kg
LD50 dermal (rabbit)	> 5000 mg/kg
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 5000 mg/l/4h

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitisation : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight
NOAEL (dermal, rat/rabbit, 90 days)	≈ 1000 mg/kg bodyweight

Aspiration hazard : Not classified

7306 - AUTOGEAR POWER MP 80W-90	
Viscosity, kinematic	162 mm²/s @40°C

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

(Z)-octadec-9-enylamine (112-90-3)	
LC50 fish 1	0,11 mg/l Pimephales promelas
EC50 Daphnia 1	0,011 mg/l Daphnia magna
EC50 96h algae (1)	0,03 mg/l Pseudokirchnerella subcapitata

Amines, C12-14-tert-alkyl (68955-53-3)	
NOEC (acute)	0,56 mg/l

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)	
LC50 fish 1	100 mg/l

EC50 Daphnia 1	10000 mg/l
EC50 72h algae (1)	3 mg/l

Mineral oil	
LC50 fish 1	> 100 mg/l Pimephales promelas
EC50 Daphnia 1	> 10000 mg/l
EC50 72h algae (1)	> 100 mg/l Scenedesmus quadricauda

12.2. Persistence and degradability

(Z)-octadec-9-enylamine (112-90-3)	
Persistence and degradability	Readily biodegradable.
Biodegradation	66 % 28 Days

Amines, C12-14-tert-alkyl (68955-53-3)	
Biodegradation	22 % (OECD TG 301D)

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)	
Persistence and degradability	Not biodegradable.
Biodegradation	31 % 28 d OECD 301F

Mineral oil	
Biodegradation	31 %

12.3. Bioaccumulative potential

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)	
Bioconcentration factor (BCF REACH)	260
Partition coefficient n-octanol/water (Log Pow)	9,2

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR)	:	Not applicable
UN-No. (IMDG)	:	Not applicable
UN-No. (IATA)	:	Not applicable
UN-No. (ADN)	:	Not applicable
UN-No. (RID)	:	Not applicable

14.2. UN proper shipping name

Proper Shipping Name (ADR)	:	Not applicable
Proper Shipping Name (IMDG)	:	Not applicable
Proper Shipping Name (IATA)	:	Not applicable
Proper Shipping Name (ADN)	:	Not applicable
Proper Shipping Name (RID)	:	Not applicable

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR)	:	Not applicable

IMDG

Transport hazard class(es) (IMDG)	:	Not applicable

IATA

Transport hazard class(es) (IATA)	:	Not applicable

ADN

Transport hazard class(es) (ADN)	:	Not applicable

RID

Transport hazard class(es) (RID)	:	Not applicable

14.4. Packing group

Packing group (ADR)	:	Not applicable
Packing group (IMDG)	:	Not applicable
Packing group (IATA)	:	Not applicable
Packing group (ADN)	:	Not applicable
Packing group (RID)	:	Not applicable

14.5. Environmental hazards

Dangerous for the environment	:	No
Marine pollutant	:	No
Other information	:	No supplementary information available

14.6. Special precautions for user

Overland transport

No data available

Transport by sea

No data available

Air transport

No data available

Inland waterway transport

No data available

Rail transport

No data available

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions
Contains no substance on the REACH candidate list
Contains no REACH Annex XIV substances
Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.
Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

15.1.2. National regulations

Germany

Water hazard class (WGK)	:	WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1)
Hazardous Incident Ordinance (12. BImSchV)	:	Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

Ministry's list of carcinogens	:	Amines, C12-14-tert-alkyl,Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] are listed
Ministry's list of mutagens	:	Amines, C12-14-tert-alkyl,Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] are listed
NON-exhaustive list of reproductive toxins - Breastfeeding	:	None of the components are listed
NON-exhaustive list of reproductive toxins - Fertility	:	None of the components are listed
NON-exhaustive list of reproductive toxins - Evolution	:	None of the components are listed

Denmark

Danish National Regulations	:	Young people below the age of 18 years are not allowed to use the product Pregnant/breastfeeding women working with the product must not be in direct contact with the product

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer

IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
PNEC	Predicted No-Effect Concentration
PBT	Persistent Bioaccumulative Toxic
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative

Full text of H- and EUH-statements:	
Acute Tox. 2 (Inhalation)	Acute toxicity (inhal.), Category 2
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Asp. Tox. 1	Aspiration hazard, Category 1
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
Skin Sens. 1A	Skin sensitisation, category 1A
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

SDS EU (REACH Annex II)

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness