

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : 73680 - SLIDEWAY POWER 68  
Product code : 73680

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Professional use  
Function or use category : Lubricants and additives

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

North Sea Lubricants B.V. B.V.  
Ampèrestraat 5  
NL- 3846AN Harderwijk  
The Netherlands  
T +31 651345369  
[support@northsealubricants.com](mailto:support@northsealubricants.com) - [www.northsealubricants.com](http://www.northsealubricants.com)

#### 1.4. Emergency telephone number

Emergency number : +31 (0)786527652  
Monday to Friday: 09:00 - 16:00 (CET)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Hazardous to the aquatic environment — Chronic Hazard, Category 3 H412

Full text of H- and EUH-statements: see section 16

##### Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Signal word (CLP) : -  
Hazard statements (CLP) : H412 - Harmful to aquatic life with long lasting effects.  
Precautionary statements (CLP) : P273 - Avoid release to the environment.  
P501 - Dispose of contents and container to an approved waste disposal plant.

#### 2.3. Other hazards

Other hazards which do not result in classification : Flammable liquids. Prolonged or repeated skin contact with the material will remove natural oils which leads to a dermatitis. Spills of this product present a serious slipping hazard.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

# 73680 - SLIDWAY POWER 68

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil substance with national workplace exposure limit(s) (BE, BG, CZ, DK, HR, NL, NO); substance with a Community workplace exposure limit	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8 REACH-no: 01-2119484627-25	50 – 75	Asp. Tox. 1, H304
Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil substance with national workplace exposure limit(s) (BG, CZ, DK, HR, NL); substance with a Community workplace exposure limit	CAS-No.: 64742-65-0 EC-No.: 265-169-7 EC Index-No.: 649-474-00-6 REACH-no: 01-2119471299-27	25 – 50	Asp. Tox. 1, H304
C16-18-(even numbered, saturated and unsaturated)-alkylamines	EC-No.: 627-034-4 REACH-no: 01-2119473797-19	0.05 – 0.5	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)
2-Ethyl-1-Hexanol substance with national workplace exposure limit(s) (NL, CH); substance with a Community workplace exposure limit	CAS-No.: 104-76-7 EC-No.: 203-234-3 REACH-no: 01-2119487289-20	0.01 – 0.1	Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Acute Tox. 3 (Inhalation:dust,mist), H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335

Full text of H- and EUH-statements: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: After adequate first aid, no further treatment is required unless symptoms reappear.
Symptoms/effects after inhalation	: After adequate first aid, no further treatment is required unless symptoms reappear.
Symptoms/effects after skin contact	: After adequate first aid, no further treatment is required unless symptoms reappear.
Symptoms/effects after eye contact	: After adequate first aid, no further treatment is required unless symptoms reappear.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Ingestion of large quantities: immediately to hospital.

# 73680 - SLIDEWAY POWER 68

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.  
Unsuitable extinguishing media : Do not use a water jet since it may cause the fire to spread.

#### 5.2. Special hazards arising from the substance or mixture

- Hazardous decomposition products in case of fire : Toxic fumes may be released.

#### 5.3. Advice for firefighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

- Protective equipment : Eliminate all ignition sources if safe to do so.  
Emergency procedures : Ventilate spillage area.

##### 6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. Wear suitable protective clothing, gloves and eye/face protection. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

- For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.  
Methods for cleaning up : Take up liquid spill into absorbent material.  
Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment.  
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store in a well-ventilated place. Keep cool.  
Storage temperature : 45 °C  
Storage area : Store in a well-ventilated place. Store away from heat.  
Special rules on packaging : Store in a closed container. Keep only in original container.

#### 7.3. Specific end use(s)

No additional information available

# 73680 - SLIDEWAY POWER 68

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### 8.1.1 National occupational exposure and biological limit values

###### 2-Ethyl-1-Hexanol (104-76-7)

###### EU - Indicative Occupational Exposure Limit (IOEL)

Local name	2-ethylhexan-1-ol
IOEL TWA	5.4 mg/m <sup>3</sup>
Regulatory reference	COMMISSION DIRECTIVE (EU) 2017/164

###### Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil (64742-65-0)

###### EU - Indicative Occupational Exposure Limit (IOEL)

IOEL TWA	5 mg/m <sup>3</sup>
IOEL STEL	10 mg/m <sup>3</sup>

###### Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil (64742-54-7)

###### EU - Indicative Occupational Exposure Limit (IOEL)

IOEL TWA	5 mg/m <sup>3</sup>
----------	---------------------

##### 8.1.2. Recommended monitoring procedures

No additional information available

##### 8.1.3. Air contaminants formed

No additional information available

##### 8.1.4. DNEL and PNEC

No additional information available

##### 8.1.5. Control banding

No additional information available

#### 8.2. Exposure controls

##### 8.2.1. Appropriate engineering controls

No additional information available

##### 8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



###### 8.2.2.1. Eye and face protection

No additional information available

###### 8.2.2.2. Skin protection

No additional information available

###### 8.2.2.3. Respiratory protection

No additional information available

###### 8.2.2.4. Thermal hazards

No additional information available

# 73680 - SLIDEWAY POWER 68

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: light yellow.
Odour	: Not available
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: -15 °C
Boiling point	: Not available
Flammability	: Not applicable
Explosive limits	: Not available
Lower explosive limit (LEL)	: Not available
Upper explosive limit (UEL)	: Not available
Flash point	: > 180 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: 68 mm <sup>2</sup> /s @40°C
Solubility	: insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50 °C	: Not available
Density	: 885.5 kg/m <sup>3</sup> @15°C
Relative density	: Not available
Relative vapour density at 20 °C	: Not available
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle aggregation state	: Not applicable
Particle agglomeration state	: Not applicable
Particle specific surface area	: Not applicable
Particle dustiness	: Not applicable

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

# 73680 - SLIDWAY POWER 68

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

#### 2-Ethyl-1-Hexanol (104-76-7)

LD50 oral (rat)	2040 mg/kg
LD50 dermal (rat)	1970 mg/kg
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	1 mg/l/4h
LC50 inhalation (rat) (Vapours - mg/l/4h)	> 0.89 mg/l/4h

#### Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil (64742-65-0)

LD50 oral (rat)	> 5000 mg/kg bodyweight
LD50 dermal (rabbit)	> 5000 mg/kg
LC50 inhalation (rat) (Vapours - mg/l/4h)	> 5.53 mg/l/4h

#### Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil (64742-54-7)

LD50 oral (rat)	> 5000 mg/kg bodyweight
LD50 dermal (rabbit)	> 5000 mg/kg
LC50 inhalation (rat) (Vapours - mg/l/4h)	> 5.53 mg/l/4h

#### C16-18-(even numbered, saturated and unsaturated)-alkylamines

LD50 oral (rat)	1689 mg/kg
LD50 dermal (rat)	> 2000 mg/kg

Skin corrosion/irritation : Not classified  
Serious eye damage/irritation : Not classified  
Respiratory or skin sensitisation : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified  
Reproductive toxicity : Not classified  
STOT-single exposure : Not classified

#### 2-Ethyl-1-Hexanol (104-76-7)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

#### C16-18-(even numbered, saturated and unsaturated)-alkylamines

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

STOT-repeated exposure : Not classified

# 73680 - SLIDEWAY POWER 68

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil (64742-65-0)</b>	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight
NOAEL (dermal, rat/rabbit, 90 days)	≈ 1000 mg/kg bodyweight

<b>Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil (64742-54-7)</b>	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight

<b>C16-18-(even numbered, saturated and unsaturated)-alkylamines</b>	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified

<b>73680 - SLIDEWAY POWER 68</b>	
Viscosity, kinematic	68 mm <sup>2</sup> /s @40°C

### 11.2. Information on other hazards

No additional information available

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.

<b>2-Ethyl-1-Hexanol (104-76-7)</b>	
LC50 - Fish [1]	17.1 mg/l <i>Leuciscus idus melanotus</i>
EC50 - Crustacea [1]	39 mg/l <i>Daphnia mag</i>
EC50 72h - Algae [1]	16.6 mg/l <i>Desmodesmus subspicatus</i>
NOEC chronic algae	5.3 mg/l <i>Desmodesmus subspicatus</i>

<b>Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil (64742-65-0)</b>	
LC50 - Fish [1]	> 100 mg/l <i>Pimephales promelas</i>
EC50 - Crustacea [1]	> 10000 mg/l <i>Daphnia magna</i>
NOEC chronic fish	1000 mg/l <i>Oncorhynchus mykiss</i>
NOEC chronic crustacea	10 mg/l <i>Daphnia magna</i>
NOEC chronic algae	> 100 mg/l <i>Pseudokirchneriella subcapitata</i>

<b>Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil (64742-54-7)</b>	
LC50 - Fish [1]	> 100 mg/l <i>Pimephales promelas</i>
EC50 - Crustacea [1]	> 10000 mg/l <i>Daphnia magna</i>
NOEC chronic fish	1000 mg/l <i>Oncorhynchus mykiss</i>
NOEC chronic crustacea	10 mg/l <i>Daphnia magna</i>
NOEC chronic algae	> 100 mg/l <i>Pseudokirchneriella subcapitata</i>

<b>C16-18-(even numbered, saturated and unsaturated)-alkylamines</b>	
LC50 - Fish [1]	0.06 mg/l

# 73680 - SLIDWAY POWER 68

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### C16-18-(even numbered, saturated and unsaturated)-alkylamines

EC50 - Crustacea [1]	0.011 mg/l
EC50 72h - Algae [1]	0.04 mg/l
NOEC chronic crustacea	0.013 mg/l

### 12.2. Persistence and degradability

#### 2-Ethyl-1-Hexanol (104-76-7)

Persistence and degradability	Readily biodegradable.
Biodegradation	100 % OECD 301C

#### Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil (64742-65-0)

Persistence and degradability	Not readily biodegradable.
Biodegradation	31 % 28 d OECD 301F

#### Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil (64742-54-7)

Persistence and degradability	Not readily biodegradable.
Biodegradation	31 % 28 d OECD 301F

### C16-18-(even numbered, saturated and unsaturated)-alkylamines

Biodegradation	66 % 28 d OECD 301B
----------------	---------------------

### 12.3. Bioaccumulative potential

#### 2-Ethyl-1-Hexanol (104-76-7)

Bioconcentration factor (BCF REACH)	25.33
Partition coefficient n-octanol/water (Log Pow)	2.9

#### Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil (64742-65-0)

Bioconcentration factor (BCF REACH)	260
Partition coefficient n-octanol/water (Log Pow)	9.2

#### Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil (64742-54-7)

Partition coefficient n-octanol/water (Log Kow)	> 4
---	-----

### C16-18-(even numbered, saturated and unsaturated)-alkylamines

Bioconcentration factor (BCF REACH)	500
Partition coefficient n-octanol/water (Log Kow)	4.33 @25 °C

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Endocrine disrupting properties

No additional information available

### 12.7. Other adverse effects

No additional information available



# 73680 - SLIDWAY POWER 68

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Product/Packaging disposal recommendations : Dispose of contents/container to an approved waste disposal plant.

### SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number or ID number</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.2. UN proper shipping name</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.3. Transport hazard class(es)</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.4. Packing group</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

#### 14.6. Special precautions for user

##### Overland transport

No data available

##### Transport by sea

No data available

##### Air transport

No data available

##### Inland waterway transport

No data available

##### Rail transport

No data available

#### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

# 73680 - SLIDWAY POWER 68

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

### 15.1.2. National regulations

No additional information available

## 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Comments
	Comments (on top of composition)	Added	
	SDS EU format	Added	
2.1	Adverse physicochemical, human health and environmental effects	Removed	
7.2	Storage temperature	Modified	
7.2	Storage conditions	Modified	
13.1	Waste disposal recommendations	Modified	

Full text of H- and EUH-statements:	
Acute Tox. 3 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.

# 73680 - SLIDWAY POWER 68

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.