

WAVE POWER PERFORMANCE 15W-40

Mineral Passenger Car Engine oil

WAVE POWER PERFORMANCE 15W-40 is a multi-functional mineral engine oil for older gasoline-, diesel- and LPG engines of passenger cars and light vans with or without turbo compressor. This product will also be suitable for applications where ACEA A3/B3 is recommended.

WAVE POWER PERFORMANCE 15W-40 is formulated on high performance virgin base stocks in combination with selected additive package to reach the following properties:

- Stable Viscosity Index.
- Fuel Consumption
- Oxidation stability
- Good protection against rust, corrosion and wear.
- Good dispersency and detergency properties.
- Good antifoam properties.

WAVE POWER PERFORMANCE 15W-40 meets the following performance criteria:

API SL/CF

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	15W-40
Density @15 °C	kg/m ³	ASTM 4052	868
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	101
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	14.4
Viscosity Index		ASTM D2270	146
Viscosity CCS @ -20 °C	cP	ASTM D5293	4204
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-37
Total Base Number	mgKOH/g	ASTM D2896	8.4
Date Issued: 4-10-2021	Supersedes: 17-6-2021	Revision Nr.: 03	

