

WAVE POWER RACING 10W-60

Fully Synthetic Passenger Car Engine oil

WAVE POWER RACING 10W-60 is a high performance fully synthetic motor oil of exceptional quality, delivering extreme performance in gasoline-, diesel- and LPG fuelled engines in passenger cars with or without turbocharger, working under severe temperatures and load conditions.

WAVE POWER RACING 10W-60 is based on high quality 100% synthetic Poly Alpha Olefin (PAO) in combination with an unique additive package to ensure the following properties:

- Excellent thermal and oxidation stability.
- Very good dispersant and detergent properties.
- Excellent cold temperature properties for a smooth cold start.
- Excellent protection against wear, corrosion and foam.
- Suited for extreme and severe conditions.

WAVE POWER RACING 10W-60 meets the following performance criteria:

API SQ ACEA A3/B4

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	10W-60
Density @ 15 °C	kg/m ³	ASTM 4052	846.6
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	160.8
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	23.9
Viscosity Index		ASTM D2270	171
Viscosity CCS @ -25 °C	cP	ASTM D5293	4580
MRV @ -30 °C	mPa.s	ASTM D4684	26019
HTHS @ 150 °C	mPa.s	ASTM D4683	5.7
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-54
Total Base Number	mgKOH/g	ASTM D2896	10.2
Sulphated Ash	%Wt	ASTM D874	1.09
Date Issued: 9-12-2025	Supersedes: 15-5-2025		Revision Nr.: 08

