

## WAVE POWER PERFORMANCE 10W-40

### Semi Synthetic Passenger Car Engine oil

**WAVE POWER PERFORMANCE 10W-40** is an universal high performance semi synthetic oil for use in gasoline- and diesel engines of passenger cars and light vans with or without turbocharger. This product is unsuitable for diesel engines equipped with a Diesel Particle Filter (DPF).

**WAVE POWER PERFORMANCE 10W-40** is formulated with high quality re-refined base stocks in combination with a special additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- High thermal and oxidation stability.
- Good resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High Viscosity Index.

**WAVE POWER PERFORMANCE 10W-40** meets the following performance criteria:

API SL/CF

### Typical Analysis

Properties	Unit	Method	Typical Value
Colour		ASTM D1500	2.5
SAE Grade		SAE J300	10W-40
Density @15 °C	kg/m <sup>3</sup>	ASTM 4052	854.3
Kinematic Viscosity @ 40 °C	mm <sup>2</sup> /s	ASTM D7042	89.3
Kinematic Viscosity @ 100 °C	mm <sup>2</sup> /s	ASTM D7042	14.2
Viscosity Index		ASTM D2270	164
Viscosity CCS @ -25 °C	cP	ASTM D5293	3900
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-39
Total Base Number	mgKOH/g	ASTM D2896	8.4
Sulphated Ash	%Wt	ASTM D874	1.05
Date Issued: 15-5-2025		Supersedes: 25-03-2021	Revision Nr.: 03

