

WAVE POWER PERFORMANCE 15W-40

Mineral Passenger Car Engine oil

WAVE POWER PERFORMANCE 15W-40 is a multi-functional mineral engine oil for older gasoline-, diesel- and LPG engines of passenger cars and light vans with or without turbo compressor. This product will also be suitable for applications where ACEA A3/B3 is recommended.

WAVE POWER PERFORMANCE 15W-40 is formulated on high performance virgin base stocks in combination with selected additive package to reach the following properties:

- Stable Viscosity Index.
- Fuel Consumption
- Oxidation stability
- Good protection against rust, corrosion and wear.
- Good dispersancy and detergency properties.
- Good antifoam properties.

WAVE POWER PERFORMANCE 15W-40 meets the following performance criteria:

API SL/CF

Typical Analysis

| Properties | Unit | Method | Typical Value |
|------------------------------|--------------------|------------------------|------------------|
| SAE Grade | | SAE J300 | 15W-40 |
| Density @15 °C | kg/m ³ | ASTM 4052 | 865.7 |
| Kinematic Viscosity @ 40 °C | mm ² /s | ASTM D7042 | 93.7 |
| Kinematic Viscosity @ 100 °C | mm ² /s | ASTM D7042 | 13.6 |
| Viscosity Index | | ASTM D2270 | 146 |
| Viscosity CCS @ -20 °C | cP | ASTM D5293 | 3870 |
| Flash Point COC | °C | ASTM D92 | >201 |
| Pour Point | °C | ASTM D7346 | -36 |
| Total Base Number | mgKOH/g | ASTM D2896 | 8.5 |
| Date Issued: 15-5-2025 | | Supersedes: 15-08-2022 | Revision Nr.: 05 |

