

## **WAVE POWER PERFORMANCE HM 10W-40**

Semi Synthetic Passenger Car Motor Oil for High Mileage engines

WAVE POWER PERFORMANCE HM 10W-40 is an universal performance semi synthetic oil for use in older (1995-2010) gasoline- and diesel engines of passenger cars and light vans with or without turbocharger specially formulated to help demands of "High-Mileage" engines which have been running for more than 100.000 km. WAVE POWER PERFORMANCE HM 10W-40 can be used in cars that require ACEA A3/B3. This product is unsuitable for diesel engines equipped with a Diesel Particulate Filter (DPF) and not intended for vehicles predating 1990 that need increased zinc/phosphorus (ZDDP) oils

**WAVE POWER PERFORMANCE HM 10W-40** is formulated with high quality refined mineral and synthetic base stocks in combination with a special additive technology to achieve the following performance:

- Very good low temperature properties.
- Maximize the life of the engine.
- Special formulated additive helps to slow down the ageing process.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level + high viscosity index.

WAVE POWER PERFORMANCE HM 10W-40 meets the following performance criteria:

API SL/CF

**Typical Analysis** 

Properties	Unit	Method	Тур	ical Value
SAE Grade		SAE J300		10W-40
Density @15°C	kg/m³	ASTM 4052		859.4
Kinematic Viscosity @ 40°C	mm <sup>2</sup> /s	ASTM D704	12	88.2
Kinematic Viscosity @ 100°C	mm <sup>2</sup> /s	ASTM D704	12	13.9
Viscosity Index		ASTM D227	70	162
Viscosity CCS @ -25°C	сР	ASTM D529	93	3980
Flash Point COC	°C	ASTM D92		>201
Pour Point	°C	ASTM D734	16	-39
Total Base Number	mgKOH/g	ASTM D289	96	7.8
Sulphated Ash	%Wt	ASTM D874		0.95
Date Issued: 5-11-2025	Supersedes: 15-5-202	5	Revision Nr.: 04	















