

WAVE POWER PERFORMANCE HM 10W-40

Semi Synthetic Passenger Car Motor Oil for High Mileage engines

WAVE POWER PERFORMANCE HM 10W-40 is an universal performance semi synthetic oil for use in older (1995-2010) gasoline- and diesel engines of passenger cars and light vans with or without turbocharger specially formulated to help demands of "High-Mileage" engines which have been running for more than 100.000 km. This product is unsuitable for diesel engines equipped with a Diesel Particulate Filter (DPF) and **not intended for vehicles predating 1990 that need increased zinc/phosphorus (ZDDP) oils.**

WAVE POWER PERFORMANCE HM 10W-40 is formulated with high quality refined mineral and synthetic base stocks in combination with a special additive technology to achieve the following performance:

- Very good low temperature properties.
- Maximize the life of the engine.
- Special formulated additive helps to slow down the ageing process
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level + high viscosity index

WAVE POWER PERFORMANCE HM 10W-40 meets the following performance criteria:

API SL/CF ACEA A3/B4

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	10W-40
Density @15 °C	kg/m ³	ASTM 4052	859.4
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	88.2
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	13.9
Viscosity Index		ASTM D2270	162
Viscosity CCS @ -25 °C	cP	ASTM D5293	3980
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-39
Total Base Number	mgKOH/g	ASTM D2896	7.8
Sulphated Ash	%Wt	ASTM D874	0.95
Date Issued: 15-5-2025		Supersedes: 19-01-2021	Revision Nr.: 03

