

## WAVE POWER EXCELLENCE 5W-40

### Fully Synthetic Passenger Car Engine oil

**WAVE POWER EXCELLENCE 5W-40** is a modern 100% synthetic engine oil for use in high output, turbocharged, supercharged multi valve fuel injected engines in passenger cars, SUVs and light vans.

**WAVE POWER EXCELLENCE 5W-40** is formulated with high quality synthetic base stocks in combination with an unique additive technology to achieve the following performance:

- Long drain intervals
- High protection against deposits and "sludge" formation
- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High Viscosity Index
- 

**WAVE POWER EXCELLENCE 5W-40** meets the following performance criteria:

<b>Approved</b>	MB-Approval 229.5	VW 502.00/505.00	
<b>Meets</b>	API SP MB 229.3 Renault RN 0700/0710	ACEA A3/B4 GM-LL-025-A PSA B71 2296	MB 226.5 GM-LL-025-B BMW LL-01 (<2019)

### Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	5W-40
Density @15 °C	kg/m <sup>3</sup>	ASTM 4052	849.8
Kinematic Viscosity @ 40 °C	mm <sup>2</sup> /s	ASTM D7042	83.7
Kinematic Viscosity @ 100 °C	mm <sup>2</sup> /s	ASTM D7042	14.3
Viscosity Index		ASTM D2270	177
Viscosity CCS @ -30 °C	cP	ASTM D5293	5400
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-33
Total Base Number	mgKOH/g	ASTM D2896	11.3
Sulphated Ash	%Wt	ASTM D874	1.25
Date Issued: 15-5-2025		Supersedes: 15-08-2022	Revision Nr.: 05

