

TIDAL POWER EHPD 10W-40

Synthetic Heavy Duty Diesel Engine Oil

TIDAL POWER EHPD 10W-40 is a high performance synthetic engine oil to be used in diesel engines in light- and heavy commercial vehicles with or without turbocharger designed for use in Euro-II, Euro-III, EURO-IV and EURO-V emission requirements and engines equipped with EGR and/or SCR exhaust after treatment system.

TIDAL POWER EHPD 10W-40 is unsuitable for diesel engines equipped with a Diesel Particulate Filter (DPF).

TIDAL POWER EHPD 10W-40 is based on high performance synthetic base oil in combination with a specially selected additive technology to ensure the following properties:

- Excellent thermal and oxidation stability.
- Excellent protection against forming of "Bore Polishing".
- Suitable for low emission engine equipped with EGR and SCR technology
- Excellent protection against wear, foam and corrosion.
- Low temperature properties, to ensure a smooth cold start.
- Extended oil drain interval possible

TIDAL POWER EHPD 10W-40 meets the following performance criteria:

Approved: MAN M3377 MACK EO-N Renault RLD-2 Volvo VDS-3
MAN M3277 DTFR 15B120 (MB 228.5) Deutz DQC IV-18

Meets: API CI-4 ACEA E4/E7 Deutz DQC-IV-10 Renault RXD
MTU Type 3 Cummins 20077/20078

**Suitable
for use** Scania LDF-2

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	10W-40
Density @15 °C	kg/m ³	ASTM 4052	862.6
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	99.1
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	14.6
Viscosity Index		ASTM D2270	153
Viscosity CCS @ -25 °C	cP	ASTM D5293	5900
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	12.4
Sulphated Ash	%Wt	ASTM D874	1.5
Date Issued: 15-5-2025		Supersedes: 25-3-2022	Revision Nr.: 08

