

TIDAL POWER HDX 20W-50

Mineral Heavy Duty Diesel Engine oil

TIDAL POWER HDX 20W-50 is an extra high performance universal engine oil designed for high loaded diesel engines in light- and heavy commercial vehicles working under severe operating conditions through the whole year for use in Euro-3, Euro-4 and Euro-5 engines equipped with EGR and/or SCR. This product is not suitable for vehicles equipped with a Diesel Particulate Filter (DPF).

TIDAL POWER HDX 20W-50 is formulated with high refined solvent mineral base stock in combination with a special additive package to reach the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- High anti-foam, anti-wear and anti-corrosion properties.
- Excellent protection against Bore Polishing.
- Extended drain intervals.

TIDAL POWER HDX 20W-50 meets the following performance criteria:

API CI-4	API SL	ACEA E7	JASO DH-1
MAN M 3275	Volvo VDS-3	Deutz DQC-III	MTU Type 2
Mack EO-N	Cummins CES 20077/20078	Caterpillar ECF-1a	Renault RLD-2
DDC 93K215	DTFR 15B110 (MB 228.3)	Caterpillar ECF-2	Global DHD-1

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	20W-50
Density @15 °C	kg/m ³	ASTM 4052	888.6
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	160.9
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	18.8
Viscosity Index		ASTM D2270	132
Viscosity CCS @ -15 °C, max.	cP	ASTM D5293	6780
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-30
Total Base Number	mgKOH/g	ASTM D2896	11.2
Sulphated Ash	%Wt	ASTM D874	1.5
Date Issued: 15-5-2025		Supersedes: 17-6-2021	Revision Nr.: 03

