

TIDAL POWER SPECIAL UHPD 10W-40

Fully Synthetic MID-SAPS Heavy Duty Diesel Engine Oil

TIDAL POWER SPECIAL UHPD 10W-40 is a fuel conserving super high performance MID SAPS oil, designed for high loaded diesel engines in light- and heavy commercial vehicles working under severe operating conditions through the whole year and running on low sulphur diesel fuel (max. 50 ppm). This product is formulated for use in Euro 5 and Euro 6 engines equipped with Diesel Particulate Filter (DPF). This product is also suitable for vehicles equipped with EGR and/or SCR after treatment system.

TIDAL POWER SPECIAL UHPD 10W-40 is formulated on high refined 100% synthetic base stock in combination with an special additive package to reach the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- High anti-foam, anti-wear and anti-corrosion properties.
- Excellent protection against "Bore Polishing".
- Extended drain intervals up to 150.000 km.
- Suitable for engines equipped with a Diesel Particulate Filter (DPF).

TIDAL POWER SPECIAL UHPD 10W-40 meets the following performance criteria:

Approved

Mack EOS-4.5
DTFR 15C110
(MB 228.51)

Volvo VDS-4.5
Deutz DQC IV-18-LA

Renault VI RLD-3

MTU Type 3.1

Meets

ACEA E4/E7/E8/E11
Detroit 93K222
Cummins CES 20081
Cummins CES 20086

API CK-4
Cat ECF-3
MAN M3775
Jaso DH-2-17

Renault VI RLD-4
Scania Low-Ash
MAN M3477
DTFR 15C100
(MB 228.31)

DAF PSQL 2.1E-LD
MTU Type 2.1
MAN M3271-1
DTFR 15C120
(MB 228.52)

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	10W-40
Density @15 °C	kg/m ³	ASTM 4052	859.7
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	94.7
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	14.4
Viscosity Index		ASTM D2270	158
Viscosity CCS @ -25 °C,	cP	ASTM D5293	6200
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	13.5
Sulphated Ash	%Wt	ASTM D874	0.98
Date Issued: 15-5-2025		Supersedes: 22-07-2022	Revision Nr.: 07

