

## STREAM POWER 2T

### 2-Stroke Motorcycle Oil

**STREAM POWER 2T** is a high quality lubricant suitable for use in air cooled 2-stroke gasoline engines deployed in variety of applications.

**STREAM POWER 2T** is based on high-quality virgin base oils in combination with a special selected additive package to obtain the following properties:

- Excellent lubricity protects against piston scuffing and premature wear of engine components
- Proven additive technology controls engine and exhaust system deposits
- Low ash formula prevents pre-ignition and spark plug fouling
- Easy miscibility with gasoline ensures stable homogeneous mixture even at low ambient temperatures.

**STREAM POWER 2T** meets the following performance criteria:

API TC

JASO FB

#### Typical Analysis

Properties	Unit	Method	Typical Value
Density @15 °C	kg/m <sup>3</sup>	ASTM D4052	879.8
Kinematic Viscosity @ 40 °C	mm <sup>2</sup> /s	ASTM D7042	71.1
Kinematic Viscosity @ 100 °C	mm <sup>2</sup> /s	ASTM D7042	9.4
Viscosity Index		ASTM D2270	111
Flash Point COC	°C	ASTM D92	160
Pour Point	°C	ASTM D7346	-30
Total Base Number	mgKOH/g	ASTM D2896	1.2
Sulphated Ash	%Wt	ASTM D874	0.25
Date Issued: 15-5-2025		Supersedes: 06-07-2023	Revision Nr.: 03

