

## AUTOGEAR POWER MP 75W-90

### Automotive Multi Purpose Gear Oil

**AUTOGEAR POWER MP 75W-90** is a high performance multi purpose gear lubricant designed to provide excellent lubrication in a wide range of automotive transmissions, axles and final drives.

**AUTOGEAR POWER MP 75W-90** is based on a high quality refined virgin base oil in combination with a special additive package to ensure the following properties:

- Good extreme pressure and anti-wear properties.
- High thermal- and oxidation stability.
- Effective rust, wear and corrosion protection.
- Better low temperature provides easy start-up at low ambient temperatures.
- Good anti-foam properties ensure film strength for effective lubrication.
- Excellent seal compatibility.

**AUTOGEAR POWER MP 75W-90** meets the following performance criteria:

API GL-5                      MIL-L-2105D                      MAN 342 M2                      Volvo STD 1273.1  
ZF TE-ML 05A, 7A, 16B, 17B, 21A

### Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J306	75W-90
Density @15 °C	kg/m <sup>3</sup>	ASTM 4052	869.0
Kinematic Viscosity @ 40 °C	mm <sup>2</sup> /s	ASTM D7042	97.6
Kinematic Viscosity @ 100 °C	mm <sup>2</sup> /s	ASTM D7042	15.0
Viscosity Index		ASTM D2270	162
Viscosity Brookfield @-55 °C	cP	ASTM D5293	114000
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-45
Date Issued: 15-5-2025		Supersedes: 27-08-2020	Revision Nr.: 1

