

AUTOGEAR POWER MP 80W-90

Automotive Multi Purpose Gear Oil

AUTOGEAR POWER MP 80W-90 is a high performance multi purpose gear lubricant designed to provide excellent lubrication in a wide range of automotive transmissions, axles and final drives.

AUTOGEAR POWER MP 80W-90 is based on a high quality refined virgin base oil in combination with a special additive package to ensure the following properties:

- Good extreme pressure and anti-wear properties.
- High thermal- and oxidation stability.
- Effective rust, wear and corrosion protection.
- Better low temperature provides easy start-up at low ambient temperatures.
- Good anti-foam properties ensure film strength for effective lubrication.
- Excellent seal compatibility.

AUTOGEAR POWER MP 80W-90 meets the following performance criteria:

API GL-5 MIL-L-2105D Volvo STD 1273.1 MAN 342 M2
ZF TE-ML 05A, 7A, 12E, 16B, 16C, 17B, 19B, 21A

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J306	80W-90
Density @15 °C	kg/m ³	ASTM 4052	885.7
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	124.9
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	14.1
Viscosity Index		ASTM D2270	112
Viscosity Brookfield @-26 °C	cP	ASTM D5293	60000
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-36
Date Issued: 15-5-2025		Supersedes: 22-01-2021	Revision Nr.: 03

