

AUTOGEAR POWER MP 85W-90

Automotive Gear Oil

AUTOGEAR POWER MP 85W-90 is a high-performance gear lubricant for use in heavy duty manual transmissions and axle drives of commercial vehicles and passenger cars.

AUTOGEAR POWER MP 85W-90 is based on a high quality refined virgin base oil in combination with a special additive package to ensure the following properties:

- Good extreme pressure and anti-wear properties.
- High thermal- and oxidation stability.
- Effective rust, wear and corrosion protection.
- Better low temperature provides easy start-up at low ambient temperatures.
- Good anti-foam properties ensure film strength for effective lubrication.
- Excellent seal compatibility.

AUTOGEAR POWER MP 85W-90 meets the following performance criteria:

API GL-4/5	MB 235.6	MAN 342-M1-M2	MIL-PRF-2105D
Volvo 97310	Volvo 97316	Volvo STD 1273.21	SAE J2360
SCANIA STO 1.0	ZF TE-ML 05A/07A/08/12E/16B/16C/17B/19B/21A		

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J306	85W-90
Density @15 °C	kg/m ³	ASTM 4052	888.3
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	154.8
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	15.9
Viscosity Index		ASTM D2270	105
Flash Point COC	°C	ASTM D92	>210
Pour Point	°C	ASTM D7346	-27
Date Issued: 15-5-2025		Supersedes: 22-01-2021	Revision Nr.: 02

