

## AUTOGEAR POWER MP 85W-140

### Automotive Gear Oil

**AUTOGEAR POWER MP 85W-140** is a high-performance gear lubricant for use in heavy duty manual transmissions and axle drives of commercial vehicles and passenger cars.

**AUTOGEAR POWER MP 85W-140** is based on a high quality refined virgin base oil in combination with a special additive package to ensure the following properties:

- Good extreme pressure and anti-wear properties.
- High thermal- and oxidation stability.
- Effective rust, wear and corrosion protection.
- Better low temperature provides easy start-up at low ambient temperatures.
- Good anti-foam properties ensure film strength for effective lubrication.
- Excellent seal compatibility.

**AUTOGEAR POWER MP 85W-140** meets the following performance criteria:

API GL-5

MIL-L-2105D

Volvo STD 1273.1

ZF TE-ML 05A, 07A, 08, 12E, 16C, 16D, 21A

### Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J306	85W-140
Density @15 °C	kg/m <sup>3</sup>	ASTM 4052	908.8
Kinematic Viscosity @ 40 °C	mm <sup>2</sup> /s	ASTM D7042	390.1
Kinematic Viscosity @ 100 °C	mm <sup>2</sup> /s	ASTM D7042	27.7
Viscosity Index		ASTM D2270	97
Flash Point COC	°C	ASTM D92	>210
Pour Point	°C	ASTM D7346	-15
Date Issued: 15-5-2025		Supersedes: 22-01-2021	Revision Nr.: 02

