

## AUTOGEAR POWER MP 80W-140

### Automotive Gear Oil

**AUTOGEAR POWER MP 80W-140** is a high-performance gear lubricant for use in heavy duty manual transmissions and axle drives of commercial vehicles and passenger cars.

**AUTOGEAR POWER MP 80W-140** is based on a high quality refined virgin base oil in combination with a special additive package to ensure the following properties:

- Good extreme pressure and anti-wear properties.
- High thermal- and oxidation stability.
- Effective rust, wear and corrosion protection.
- Better low temperature provides easy start-up at low ambient temperatures.
- Good anti-foam properties ensure film strength for effective lubrication.
- Excellent seal compatibility.

**AUTOGEAR POWER MP 80W-140** meets the following performance criteria:

API GL-5	MB 235.0	MIL-L-2105D	MAN 342 M1
Volvo 97310	Volvo 97316	Voith 3.325-339	
ZF TE-ML 07A, 08, 16B/C/D, 17B, 19B, 21A			

### Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J306	80W-140
Density @15 °C	kg/m <sup>3</sup>	ASTM 4052	896.3
Kinematic Viscosity @ 40 °C	mm <sup>2</sup> /s	ASTM D7042	243.8
Kinematic Viscosity @ 100 °C	mm <sup>2</sup> /s	ASTM D7042	26.5
Viscosity Index		ASTM D2270	141
Flash Point COC	°C	ASTM D92	>210
Pour Point	°C	ASTM D7346	-33
Date Issued: 15-5-2025		Supersedes: 16-6-2021	Revision Nr.: 02

