

## **AUTOGEAR POWER LS 80W-90**

## "Limited Slip" Automotive Gear Oil

**AUTOGEAR POWER LS 80W-90** is an extra high performance extreme pressure type automotive gear lubricant specially developed for use in modern high performance passenger cars, sports utility vehicles, vans and light duty trucks with limited slip differentials.

**AUTOGEAR POWER LS 80W-90** is based on a high quality mineral virgin base oil in combination with a special additive package to ensure the following properties:

- Exceptional thermo-oxidative stability.
- Exceptional load bearing characteristics.
- Effective rust and corrosion protection.
- Excellent limited slip performance to reduce chatter and improves traction.
- Outstanding low temperature fluidity provides smoother shifting at low ambient temperatures.
- Exceptional shear stable.
- Good frictional properties provide improved fuel economy and smoother shift ability

AUTOGEAR POWER LS 80W-90 meets the following performance criteria:

API GL-5	MAN 342 M2	Volvo 1273.1	MIL-L-2105D
ZF TE-ML 05C, 07A,			

## **Typical Analysis**

Properties	Unit	Method		Typical Value	
SAE Grade		SAE J306		80W-90	
Density @15°C	kg/m³	ASTM 4052		885.1	
Kinematic Viscosity @ 40°C	mm²/s	ASTM D7042		124.0	
Kinematic Viscosity @ 100°C	mm²/s	ASTM D7042		13.9	
Viscosity Index		ASTM D2270		110	
Flash Point COC	°C	ASTM D92		>200	
Pour Point	°C	ASTM D7346		-33	
Date Issued: 15-5-2025	Supersedes: 26-1-2021		Revision Nr.: 03		