

ATF POWER ECOMAT

Automatic transmission fluid

ATF POWER ECOMAT is a high performance fully synthetic fuel economy automatic transmission fluid specially designed for long drain 6-speeds transmission for city buses. **ATF POWER ECOMAT** is recommended to use for ZF Ecomat- and ZF Ecolife transmissions.

ATF POWER ECOMAT is formulated on high refined 100% synthetic base stock in combination with an unique additive package to reach the following properties.

- Lower service cost through increased oil change interval.
- High level of anti-wear protection.
- Extended thermal- and oxidation stability.
- Limited viscosity increase.
- Prevents acid formation and soft metal corrosion.
- Friction durability leading to good shift performance and drivability even at end of drain interval.
- Avoid sludge formation that could lead to sluggish transmission operation.

ATF POWER ECOMAT meets the following performance criteria:

Voith H55.6335.xx
Volvo 97342
MB 236.9
MB 236.93
DTRF 13C170
GM D-IID / D-IIH

Voith 150.014524.xx
Volvo 97341
MAN 339 Z1/Z2/Z3/Z11/Z12
MB 236.81
DTRF 13C160
ZF TE-ML 04D / 14A/B/C / 20B/C / 25B/C

Voith H55.6336.xx
Volvo 97340
MAN 339 V1/V2/V3
MB 236.2
DTRF 13C120

Typical Analysis

| Properties | Unit | Method | Typical Value |
|------------------------------|--------------------|-----------------------|------------------|
| Color | | visual | Amber |
| Density @15 °C | kg/m ³ | ASTM 4052 | 842.0 |
| Kinematic Viscosity @ 40 °C | mm ² /s | ASTM D7042 | 39.7 |
| Kinematic Viscosity @ 100 °C | mm ² /s | ASTM D7042 | 7.3 |
| Viscosity Index | | ASTM D2270 | 152 |
| Flash Point COC | °C | ASTM D92 | >201 |
| Pour Point | °C | ASTM D7346 | -51 |
| Date Issued: 16-3-2026 | | Supersedes: 15-5-2025 | Revision Nr.: 04 |

