

ATF POWER MV

Synthetic technology Automatic Transmission Fluid

ATF POWER MV is a high quality synthetic technology fluid specially designed with advanced multi-vehicle additive technology to serve a broad range of transmissions. **ATF POWER MV** exceeds the complex requirements of Automatic Transmission/ Vehicle Manufacturers of Europe, North America and Asia including the JASO 1-A performance standard created by Japanese Automobile Manufacturers Association.

Remark: Not suitable for use in Continuously Variable Transmissions (CVT), Dual Clutch Transmission (DCT), Daimler MB 7 speed (NAG 2), ZF 6 Speed.

ATF POWER MV is formulated with high quality synthetic technology base stocks in combination with a special additive technology to achieve the following performance:

- Excellent thermo- and oxidation stability.
- Improved anti-shudder properties, torque capacity, low temperature properties coupled with balanced frictional stability provides better shift feel and drivability.
- Excellent anti-corrosion, foam inhibition and seal protection.
- Extremely high Viscosity Index and shear stability ensures adequate lubrication over entire service life in both high operating & low starting temperatures.

ATF POWER MV meets the following performance criteria:

Allison C4, TES 295	LT 71141, LA 23634	ETL -7045E, 8072B	Cat TO-2
Chrysler +3, +4	Ford Mercon	Ford Mercon V	Dexron IID, IIIG/H
Honda SP-III, Z1	Mitsubishi SP-III	KIA SP-III	Idemitsu K17
JWS 3309/3314/3317	JASO M315-2004	Texaco N402	MAN 3391 V1/Z2
Mazda ATF M-III, M5	MB 236.3, 5, 6, 9	MB 236.10, 11	Nissan Matic D,J,K,W
Subaru ATF, HP	Toyota T-III, T-IV	Voith H55.6335.xx	Volvo Std 1273.4
VW G 052 025	VW G 052 055	VW G 052 162	VW G 052 990
Volvo P/N 1161521	Volvo 1161540	Volvo 1161640	Volvo CE 1273,41
Ssang Yong DSIH 5M-66	ZF TE ML 03D, 04D, 11A/B, 14A/B, 16L/R, 17C, 20B, 25B		

Typical Analysis

Properties	Unit	Method	Typical Value
Color		visual	Amber
Density @15 °C	kg/m ³	ASTM 4052	846.7
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	35.5
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	7.6
Viscosity Index		ASTM D2270	188
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-51
Date Issued: 15-5-2025		Supersedes: 17-6-2021	Revision Nr.: 02

