

ATF POWER CVT

Automatic transmission fluid

ATF POWER CVT is an ultra-high performance CVT fluid formulated with selected synthetic technology base stocks and specially developed for use in the latest generation of Continuously Variable Transmission (CVT) – gearboxes which transfer traction via steel-made traction chain or push-belts.

ATF POWER CVT is formulated on highly refined synthetic technology base stocks in combination with an unique additive package to reach the following properties.

- Good thermo-and oxidation stability.
- Extended drain interval possible.
- Excellent anti-wear, antirust and anticorrosion technology.
- High Viscosity Index ensures adequate lubrication in both high operating & low starting temperatures.
- Better foam control leads to smooth & lasting shift feel and reduces fluid loss.
- Enhanced low temperature fluidity assist in good cold start performance.
- Compatibility with all common seal materials

ATF POWER CVT meets the following performance criteria:

Audi/VW G 052 180	Ford Mercon C	Daihatsu Ammix CVTF-DC, CVTF-DFE
Audi/VW G 052 516	Ford M2C928-A	Ford WSS-M2C933-A
BMW EZL 799A	Honda HCF-2	Honda Genuine CVT Fluid
FCA CVTF+4	Hyundai/Kia SP CVT-1	Honda Multi Matic Fluid (HMMF)
GM DEX-CVT	MB 236.20	Mazda CVTF 3320 / JWS 3320
GM CVT	Nissan NS-1/NS-2/NS-3	Mitsubishi Dia Queen CVTF J1 / J4
Subaru e-CVTF	Subaru High Torque CVTF	Subaru Lineartronic CVTF / CVTF-II
Subaru i-CVT F / FG	Suzuki CVTF 3320	Suzuki CVT Fluid Green 1 / 2
Toyota TC	Toyota FE	Toyota WS (JWS3324)

Typical Analysis

Properties	Unit	Method	Typical Value
Color		visual	Amber
Density @15 °C	kg/m ³	ASTM 4052	848.7
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	34.3
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	7.0
Viscosity Index		ASTM D2270	174
Flash Point COC	°C	ASTM D92	>180
Pour Point	°C	ASTM D7346	-51
Date Issued: 15-5-2025		Supersedes: 17-6-2021	Revision Nr.: 03

