

SUPER TRACTOR POWER 10W-40

Super Tractor Oil Universal (STOU)

SUPER TRACTOR POWER 10W-40 is a high quality universal synthetic technology based so called "Super Tractor Oil Universal" (STOU) developed for use in tractors, combines, harvesters and off the road equipment with or without turbocharger diesel engines. Super Tractor Oil Universal is also designed to lubricate the transmission, power take-off, final drive, hydraulic system and oil immersed "wet brakes". This product cannot be used in diesel engines equipped with a Diesel Particulate Filter (DPF).

SUPER TRACTOR POWER 10W-40 is formulated on high refined synthetic technology hydrocracked base stocks in combination with an unique additive package to reach the following properties.

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- Excellent cold start properties.
- High anti-foam, anti-wear and anti-corrosion properties.
- Suitable for wet brakes.

SUPER TRACTOR POWER 10W-40 meets the following performance criteria:

Engine Spec:	API CG-4/CF-4/CE/SF	MB 227.1	ACEA E3
UTTO/STOU Spec:	JD J20C, J20D, J27	Ford M2C86B, 134D	Ford M2C159B / C
	Case MS 1204, 6, 7, 9	MF M 1135/1139/1143/1144/1145	
	CAT TO-2	API GL-4	Allison C4
	ZF TE-ML 06A, 06B, 06C, 06D, 06E, 06H 07B		NH 82009201, 2, 3
Hydr. Spec:	Eaton M-2950S	Eaton I-280-S	Danfoss

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	10W-40
Density @15 °C	kg/m ³	ASTM 4052	859.7
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	92.6
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	14.3
Viscosity Index		ASTM D2270	160
Viscosity CCS @ -25 °C	cP	ASTM D5293	5200
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-39
Total Base Number	mgKOH/g	ASTM D2896	10.5
Date Issued: 15-5-2025		Supersedes: 10-6-2021	Revision Nr.: 02

