

## SUPER TRACTOR POWER 15W-40

### Mineral Heavy Duty Diesel Engine oil

**SUPER TRACTOR POWER 15W-40** is a high quality universal mineral based so called "Super Tractor Oil Universal" (STOU) developed for use in tractors, combines, harvesters and off the road equipment with or without turbocharger diesel engines. Super Tractor Oil Universal is also designed to lubricate the transmission, power take-off, final drive, hydraulic system and oil immersed "wet brakes". This product cannot be used in diesel engines equipped with a Diesel Particulate Filter (DPF).

**SUPER TRACTOR POWER 15W-40** is formulated on high refined solvent mineral base stock in combination with an unique additive package to reach the following properties.

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- Excellent cold start properties.
- High anti-foam, anti-wear and anti-corrosion properties.
- Suitable for wet brakes.

**SUPER TRACTOR POWER 15W-40** meets the following performance criteria:

<b>Engine Spec</b>	API CG-4/CF-4/CE/SF	MB 227.1	ACEA E3
<b>UTTO/STOU Spec</b>	JD J20C/D	Ford M2C86B/C	Ford M2C 134-A/C/D
	Ford M2C159B/C	FNH 82009201	Allison C-4
	Case MS 1204/6/7/9	MF M 1135/1139	MF M 1143/1145
	Cat TO-2	API GL-4	MF 1127-A
	FNH-2-C-201.00	NH 410-B	NH 420-A
	ZF TE-ML 05K, 06B/C, 07B/D		
<b>Hydr. Spec</b>	Eaton M-2950S	Eaton I-280-S	Danfoss

### Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	15W-40
Density @15 °C	kg/m <sup>3</sup>	ASTM 4052	883.1
Kinematic Viscosity @ 40 °C	mm <sup>2</sup> /s	ASTM D7042	96.6
Kinematic Viscosity @ 100 °C	mm <sup>2</sup> /s	ASTM D7042	13.5
Viscosity Index		ASTM D2270	140
Viscosity CCS @ -20 °C,	cP	ASTM D5293	5800
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-39
Total Base Number	mgKOH/g	ASTM D2896	10.5
Sulphated Ash	%Wt	ASTM D874	1.5
Date Issued: 15-5-2025		Supersedes: 10-6-2021	Revision Nr.: 02

