

AUTOGEAR POWER TX 75W-80

Fully Synthetic Universal Transmission Oil

AUTOGEAR POWER TX 75W-80 is a high-quality fuel saving synthetic thermally stable long life gear lubricant designed for passenger- and commercial vehicles using manual transmissions fitted with different synchronizers including latest ones based on carbon.

AUTOGEAR POWER TX 75W-80 is based on high quality synthetic base oil in combination with a special additive package to ensure the following properties:

- Exceptional thermo-oxidative stability
- Superior lubricating properties provide improved fuel economy
- Exceptional load bearing characteristics
- Effective rust and corrosion protection
- Outstanding low temperature fluidity provides smoother shifting at low ambient temperatures
- Good gear engagement with a variety of synchronizer materials including latest carbon
- Good frictional properties provide improved fuel economy and smoother shift ability

AUTOGEAR POWER TX 75W-80 meets the following performance criteria:

Meets: API GL-4 MAN 341 Z4 DAF
 IVECO RENAULT B0032/2
 ZF TE-ML 01L, 02L, 08, 13, 16K, 24A

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	75W-80
Density @15 °C	kg/m ³	ASTM 4052	855.6
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	56.9
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	9.7
Viscosity Index		ASTM D2270	157
Brookfield Viscosity @-40 °C	cP	ASTM D2983	100000
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-42
Date Issued: 15-5-2025		Supersedes: 17-02-2021	Revision Nr.: 04

