

AUTOGEAR POWER MTF 75W-90

Manual transmission fluid

AUTOGEAR POWER MTF 75W-90 is a high quality manual transmission fluid designed for passenger- and light commercial vehicles using both manual transmissions and transaxles. Not suitable for differentials and other API GL-5 applications.

AUTOGEAR POWER MTF 75W-90 is based on high quality synthetic technology base oil in combination with a special additive package to ensure the following properties:

- Exceptional thermo-oxidative stability.
- Superior lubricating properties provide improved fuel economy.
- Exceptional load bearing characteristics.
- Effective rust and corrosion protection.
- Outstanding low temperature fluidity provides smoother shifting at low ambient temperatures.
- Good gear engagement with a variety of synchronizer materials including brass, carbon, sintered bronze and molybdenum

AUTOGEAR POWER MTF 75W-90 meets the following performance criteria:

API GL-5	BMW MTF LT-4	Ford WSD-M2C200-C	Ford WSS-M2C200-D2
GM 1940182	GM 1940764	GM 1940004	VW G50 (VW 501 50)

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J306	75W-90
Density @15 °C	kg/m ³	ASTM 4052	868.9
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	87.9
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	14.9
Viscosity Index		ASTM D2270	179
Brookfield Viscosity @-40 °C	cP	ASTM D2983	<150000
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-42
Date Issued: 15-5-2025		Supersedes: 16-6-2021	Revision Nr.: 02

